
# HíVazo **Quick Start**





Model No: ITV201P Item No: HO-WT-2Z

#### Note before installation



Do not use tools for installation



For outdoor use with cold water only



Clean the water inlet filter regularly



Please place the timer indoors in advance to prevent frost in anticipation of freezing


## 1 Check the water inlet filter

The filter prevents impurities from entering and blocking the valve, and its peripheral rubber ring seals the connection to avoid leaks. Please install the water inlet filter correctly as shown below.



## Insert the batteries correctly

Requires 2 new AAA alkaline batteries (not included). Tightly reinstall the battery tray to ensure waterproofing.






#### Warning:

- 1. Keep the faucet off and install the timer on it (hand tight only).
- 2. Ensure the water inlet is higher than all water outlets.
- 3. The display should be as vertical as possible to the ground to prevent rainwater infiltration.

Tips: In order to ensure no water leaks, we recommend that wrap Teflon tape around the threads of the faucet or hose.











Keep the faucet off and turn the dial to "ON", Press and hold the "OK" button to manually turn the valve on, after hearing a "click" or 5 seconds, turn the dial to "OFF" to close the valve. Repeat the above operation 3~5 times. The timer has 2 zone outlets, repeat the above for each outlet separately (press the "ZONE" button to switch zones).
\*See the user manual for details.

## Check for water leaks before use

Keep away from the timer water outlet to avoid splashing water, and turn on the faucet gently.

Check: ① Check whether the water inlet is leaking.

② Repeat step 4 to check whether water flows out or closes when the valve is opened or closed.

# 6 Congratulations!

You have completed the installation of the timer. Now please see the user manual to start programming your watering schedule.



Problem	Possible Cause	Possible Solution
The water inlet leakage	1. No filter or not be placed horizontally 2. The faucet is not the standard 3/4"	1. Add a filter and make sure it's placed horizontally in the inlet. 2. Make sure the faucet is a standard 3/4" faucet. 3. Wrap Teflon tape on the tap making it tight.
The water won't stop /flow out	Long-term storage and transportation make the valve inactive      Valve blockage	Step 1. Keep the faucet turned off and turn the timer dial to "ON".  Step 2. Hold the "OK" button into manual mode, press "Zone" button to switch the zone,run watering for 3-5s and turn the dial to "OFF" to stop.  Step 3. Repeat the Step 2 for 5 to 7 times.  Step 4. Try using it normally.
Low water pressure	Filter blockage     Inlet pressure     not sufficient to     support     watering needs	1. Check if the filter is clogged, if so, clean or replace the filter. 2. Make sure the timer is installed properly and not cross-threaded. 3. Installation of a booster pump or other auxiliary equipment of increasing pressure

### **Warranty**

We provides a 1-year limited warranty on this product against manufacturing defects in materials and workmanship. If you contact us to register and activate the warranty, you can get a longer warranty period.

## Need help?

If it doesn't work and you want to return or replace it, please contact us for support during the warranty period.